



## prisma20A

APAP therapy device



### Therapy flexibility for Obstructive Sleep Apnea (OSA)

With the help of Forced Oscillation Technique (FOT), prisma20A distinguishes between obstructive and central events. In response to events, prisma20A automatically provides continuous pressure adjustments tailored exactly to the patient's needs and thus delivers highly effective treatment. Equipped with the option of combining both CPAP and APAP modes with the comfortable pressure relief softPAP, prisma20A offers a high degree of therapy flexibility. That is our APAP therapy Made in Germany.

- Comfort functions such as softSTART and autoSTART-STOP
- Heated breathing tube prismaHYBERNITE
- Easy-to-use accessories

### Major features

- Identification of periodic breathing, RERA, snoring, hypopnea, apnea and flow limitations
- Continuous check of mask, automatic mask recognition and mask test
- High-resolution therapy data for 14 days and detailed statistics for 366 days
- With SD card and USB port, optional modem for telemedicine
- Eight clearly distinguished analog signals for PSG feed
- Digital prisma connection (DPC)
- Remote management (prismaTSlab) via LAN with therapy software prismaTS
- More comfortable breathing: CPAP with pressure relief softPAP, now also for inspiration support at low pressures (softPAP 3)

prismaLINE. A platform to trust

**prismaLINE is the intelligent system solution for treatment of respiratory disorders.**

The prismaLINE represents a new dimension in operating convenience. The combination of a large monitor (touch screen or LED) and smart Graphical User Interface allows more intuitive and faster use than ever before.

This exceptional operating concept is found throughout the prismaLINE portfolio. Every prismaLINE device provides the user with ideal support for all kinds of work processes and for connectivity and accessories too.

prismaLINE offers the right device for every type of therapy in Löwenstein Medical quality: precise, reliable and unheard-of stillness.

prismaLINE: Synonymous with modern sleep therapy Made in Germany.

## Accessories



prismaAQUA – WM 29680  
Humidifier



prismaCONNECT  
WM 29670



prismaPSG – WM 29690  
PSG Module

## Accessories (not shown)

Inverter 24V, lorry – WM 24617  
 Inverter 12V, car – WM 24616  
 prismaTS – WM 93335  
 Therapy software, complete with USB data cable  
 Bacteria filter – WM 24476  
 Set of 12 pollen filters – WM 29652  
 Breathing tube, Ø 22 mm – WM 24445  
 Breathing tube, Ø 15 mm – WM 29988  
 Autoclavable breathing tube, Ø 22 mm – WM 24667  
 Heated breathing tube,  
 prismaHYBERNITE, Ø 15 mm – WM 29083  
 prismaHYBERNITE, Ø 22 mm – WM 29067  
 prisma CHECK, SpO<sub>2</sub> module – WM 29390

You'll find more information about our therapy solutions, accessories and mask systems at [loewensteinmedical.de](http://loewensteinmedical.de)

## Technical data

Product class as per Directive 93/42/EEC	IIa	Classification as per EN 60601-1-11	
Dimensions (W×H×D)	170 × 135 × 180 mm	• Type of protection from electric shock	protection class II
Weight	about 1.4 kg	• Level of protection from electric shock:	type BF
Temperature range		• Protection from damaging ingress of water and solids:	IP21
• Operation:	+5 °C to +40 °C	Alarms	leak and disconnection
• Storage:	-25 °C to +70 °C	Mean sound pressure/ Operation as per ISO 80601-2-70	about 26.5 dB(A) at 10 hPa (corresponds to sound pressure of 34.5 dB(A))
Permitted humidity, operation and storage	rel. humidity 10 % to 95 %, no condensation	CPAP/APAP operating pressure range	4 to 20 hPa
Air pressure range	700 – 1060 hPa corresponds to altitude of 3000 meters	Pressure accuracy	< 20 hPa ± 0.6 hPa
Diameter of breathing tube	22 mm or 15 mm	Peak flow as per ISO 80601-2-70, modes CPAP and APAP, without humidifier	
Electric rating	max. 40VA	4.0 hPa	235 l/min
System interface	12V DC max. 10VA	8.0 hPa	230 l/min
Power consumption in	230V 115V	12.0 hPa	220 l/min
• Operation (therapy):	0.11 A 0.22 A	16.0 hPa	215 l/min
• Standby:	0.036 A 0.019 A	20.0 hPa	210 l/min
		Stability of the dynamic pressure (short-term accuracy) for 10 breaths/min as per ISO 17510-1:2007 with use of the 22-mm tube.	
		7.0 hPa	Δp ≤ 0.24 hPa
		10.0 hPa	Δp ≤ 0.28 hPa
		13.5 hPa	Δp ≤ 0.3 hPa
		20.0 hPa	Δp ≤ 0.4 hPa

Device description  
prisma20A

Ord. Nr.  
WM 29600



Please refer to the current price list.

Löwenstein Medical Technology  
 Kronsaaßweg 40, 22525 Hamburg  
 Germany  
 T: +49 40 54702-0  
 F: +49 40 54702-461  
 info@loewensteinmedical.de  
 www.loewensteinmedical.de

